

**Surface Mount Superfast Recovery Rectifier**

**Reverse Voltage – 50 to 600 V**

**Forward Current – 1 A**

**FEATURES**


- For surface mounted applications
- Low profile package
- Glass Passivated Chip Junction
- Superfast reverse recovery time
- Lead free in comply with EU RoHS 2011/65/EU directives

**MECHANICAL DATA**

- Case: SMA
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.055g / 0.002oz

**PINNING**

| PIN | DESCRIPTION |
|-----|-------------|
| 1   | Cathode     |
| 2   | Anode       |



**Absolute Maximum Ratings and Characteristics**


Ratings at 25 °C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate current by 20%.

| Parameter  | Symbols         | ES1A       | ES1B | ES1C | ES1D | ES1E | ES1G | ES1J | Units            |                    |
|--|-----------------|------------|------|------|------|------|------|------|------------------|--------------------|
| Maximum Repetitive Peak Reverse Voltage  | $V_{RRM}$       | 50         | 100  | 150  | 200  | 300  | 400  | 600  | V                |                    |
| Maximum RMS voltage  | $V_{RMS}$       | 35         | 70   | 105  | 140  | 210  | 280  | 420  | V                |                    |
| Maximum DC Blocking Voltage  | $V_{DC}$        | 50         | 100  | 150  | 200  | 300  | 400  | 600  | V                |                    |
| Maximum Average Forward Rectified Current  | $I_{F(AV)}$     | 1          |      |      |      |      |      |      | A                |                    |
| Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)                                | $I_{FSM}$       | 30         |      |      |      |      |      |      | A                |                    |
| Maximum Forward Voltage at 1 A   | $V_F$           | 1          |      |      |      | 1.25 |      | 1.70 | V                |                    |
| Maximum DC Reverse Current at Rated DC Blocking Voltage<br>$T_a = 25\text{ }^\circ\text{C}$<br>$T_a = 125\text{ }^\circ\text{C}$ | $I_R$           | 5          |      |      |      | 100  |      |      | $\mu\text{A}$    |                    |
| Typical Junction Capacitance at $V_R=4\text{V}$ , $f=1\text{MHz}$  | $C_j$           | 15         |      |      |      |      |      |      |                  | pF                 |
| Maximum Reverse Recovery Time <sup>(1)</sup>   | $t_{rr}$        | 35         |      |      |      |      |      |      |                  | ns                 |
| Typical Thermal Resistance <sup>(2)</sup>  | $R_{\theta JA}$ | 75         |      |      |      |      |      |      |                  | $^\circ\text{C/W}$ |
| Operating and Storage Temperature Range  | $T_j, T_{stg}$  | -55 ~ +150 |      |      |      |      |      |      | $^\circ\text{C}$ |                    |


(1) Measured with  $I_F = 0.5\text{ A}$ ,  $I_R = 1\text{ A}$ ,  $I_{rr} = 0.25\text{ A}$ .

(2) P.C.B. mounted with 1.0 X 1.0" (2.54 X 2.54 cm) copper pad areas.


**Fig.1 Reverse Recovery Time Characteristic And Test Circuit Diagram**




Note: 1. Rise Time = 7ns, max.  
Input Impedance = 1megohm, 22pF.  
2. Rise Time = 10ns, max.  
Source Impedance = 50 ohms.




**Fig.2 Maximum Average Forward Current Rating**




**Fig.3 Typical Reverse Characteristics**




**Fig.4 Typical Forward Characteristics**



**Fig.5 Typical Junction Capacitance**




**Fig.6 Maximum Non-Repetitive Peak Forward Surge Current**




## PACKAGE OUTLINE

Plastic surface mounted package; 2 leads



| UNIT |     | A   | D   | E   | H <sub>E</sub> | c    | e   | g   | a   |
|------|-----|-----|-----|-----|----------------|------|-----|-----|-----|
| mm   | max | 2.2 | 4.5 | 2.7 | 5.2            | 0.31 | 1.6 | 1.5 | 0.3 |
|      | min | 1.9 | 4.0 | 2.3 | 4.7            | 0.15 | 1.3 | 0.9 |     |
| mil  | max | 87  | 181 | 106 | 205            | 12   | 63  | 59  | 12  |
|      | min | 75  | 157 | 91  | 185            | 6    | 51  | 35  |     |

### The recommended mounting pad size



Unit :  $\frac{\text{mm}}{\text{mil}}$

### Marking

| Type number | Marking code |
|-------------|--------------|
| ES1A        | ES1A         |
| ES1B        | ES1B         |
| ES1C        | ES1C         |
| ES1D        | ES1D         |
| ES1E        | ES1E         |
| ES1G        | ES1G         |
| ES1J        | ES1J         |